

SPEAKER IC SERIES

IC100

► Technical Data


| | |
|------------------|---|
| Impedance | 6 Ω |
| Frequency Range | -6 db 120 Hz – 20 kHz |
| System | Line array speaker |
| Broadband Driver | 3 x (20 x 120 mm) |
| Rated Driver | 30 W |
| Maximum Power | 60 W |
| Crossover Point | Passive: BEC Crossover Active: Bessel 6 db, 180 Hz |

► Radiation

| | |
|-------------------------|------------------|
| Radiation angle, Horiz. | 180° |
| Radiation angle, Vert. | 40° |
| Sensitivity | 86 dB / W / 1 m |
| Max. Rated SPL | 102 dB / W / 1 m |

► Housing

| | |
|---------------------|--|
| Material | Aluminium |
| Color | Black, White, Silver, Gold special on request |
| Number of Drivers | 3 |
| Mounting (included) | Metal Angle Bracket |
| Mounting (optional) | Ceiling Mount, In-Wall Mounting, Magnetic On-Wall Bracket, Stacking Adapter |
| Operating Temp. | 0 – 100° C |
| Dimensions | 37,5 x 998 x 23 mm |
| Weight | 1.0 kg |
| Input Connectors | Phoenix 2-pole, RM: 5,08 mm |



IC100 Black – 4262477791584
IC100 White – 4262477791577
IC100 Silver – 4262477791508
IC100 Gold – 4262477791287