

SPEAKER IC-WP SERIES

IC28-WP

WATERPROOF**Q3 2026**

► Technical Data


Impedance	8 Ω / 16 Ω
Frequency Range	-6 db 120 Hz – 20 kHz
System	Line array speaker
Broadband Driver	1 x (20 x 120 mm)
Rated Driver	10 W
Maximum Power	20 W
Crossover Point	Passive: BEC Crossover Active: Bessel 6 db, 180 hz

► Radiation

Radiation angle, Horiz.	180°
Radiation angle, Vert.	40°
Sensitivity	83 dB
Max. Rated SPL	95 dB

► Housing

Material	Aluminium
Color	Black, White
Number of Drivers	1
Mounting (included)	Metal Angle Bracket
Mounting (optional)	Ceiling Mount, In-Wall Mounting, Magnetic On-Wall Bracket, Stacking Adapter
Operating Temp.	0 – 100° C
Dimensions	37,5 x 280 x 23 mm
Weight	300 g
Fixed cable connection	2 x 1,0 mm ²



IC28-WP Black (8 Ω) – 4262477792154
IC28-WP White (8 Ω) – 4262477792161
IC28-WP Black (16 Ω) – 4262477791003
IC28-WP White (16 Ω) – 4262477790990