

SPEAKER IC SERIES

IC100

► Technical Data


Impedance	6 Ω
Frequency Range	-6 db 120 Hz – 20 kHz
System	Line array speaker
Broadband Driver	3 x (20 x 120 mm)
Rated Driver	30 W
Maximum Power	60 W
Crossover Point	Passive: BEC Crossover Active: Bessel 6 db, 180 Hz

► Radiation

Radiation angle, Horiz.	160°
Radiation angle, Vert.	40°
Sensitivity	86 dB / W / m
Max. Rated SPL	102 dB / W / m

► Housing

Material	Aluminium
Color	Black, White, Silver, Gold special on request
Number of Drivers	3
Mounting	Metal angle bracket (included)
Optional	In-Wall mounting Magnetic wall bracket Stacking adapter
Operating Temp.	0 – 100° C
Dimensions	37,5 x 998 x 23 mm
Weight	1.0 kg
Input Connectors	Phoenix 2-pole, RM: 5,08 mm



IC100 Center Black – 714109108377	IC100 Black – 714109108558
IC100 Center White – 714109108381	IC100 White – 714109108561
IC100 Center Silver – 714109108386	IC100 Silver – 714109108614
IC100 Center Gold – 4262477791294	IC100 Gold – 4262477791287