

SPEAKER IC SERIES

IC50

► Technical Data

Impedance	8 Ω
Frequency Range	-6 db 120 Hz – 20 kHz
System	Line array speaker
Broadband Driver	2 x (20 x 120 mm)
Rated Driver	20 W
Maximum Power	40 W
Crossover Point	Passive: BEC Crossover Active: Bessel 6 db, 180 Hz

► Radiation

Radiation angle, Horiz.	160°
Radiation angle, Vert.	40°
Sensitivity	86 dB / W / m
Max. Rated SPL	98 dB / W / m

► Housing

Material	Aluminium
Color	Black, White, Silver, Gold special on request
Number of Drivers	2
Mounting	Metal angle bracket (included)
Optional	In-Wall mounting Magnetic wall bracket Stacking adapter
Operating Temp.	0 – 100° C
Dimensions	37,5 x 498 x 23 mm
Weight	500 g
Input Connectors	Phoenix 2-pole, RM: 5,08 mm



IC50 Center Black	– 714109108409	IC50 Black	– 714109108590
IC50 Center White	– 714109108435	IC50 White	– 714109108595
IC50 Center Silver	– 714109108462	IC50 Silver	– 714109108626
IC50 Center Gold	– 714109108441	IC50 Gold	– 714109108619