

SPEAKER IC SERIES

IC70

► Technical Data


Impedance	6 Ω
Frequency Range	-6 db 120 Hz – 20 kHz
System	Line array speaker
Broadband Driver	3 x (20 x 120 mm)
Rated Driver	30 W
Maximum Power	60 W
Crossover Point	Passive: BEC Crossover Active: Bessel 6 db, 180 Hz

► Radiation

Radiation angle, Horiz.	160°
Radiation angle, Vert.	40°
Sensitivity	86 dB / W / m
Max. Rated SPL	102 dB / W / m

► Housing

Material	Aluminium
Color	Black, White, Silver, Gold special on request
Number of Drivers	3
Mounting	Metal angle bracket (included)
Optional	In-Wall mounting Magnetic wall bracket Stacking adapter
Operating Temp.	0 – 100° C
Dimensions	37,5 x 698 x 23 mm
Weight	700 g
Input Connectors	Phoenix 2-pole, RM: 5,08 mm



IC70 Center Black – 714109108392	IC70 Black – 714109108572
IC70 Center White – 714109108393	IC70 White – 714109108581
IC70 Center Silver – 714109108402	IC70 Silver – 714109108615
IC70 Center Gold – 4262477791454	IC70 Gold – 4262477791447